

**General ordering data**

|                       |                                   |
|-----------------------|-----------------------------------|
| Type                  | Terminal block RSA PE 4 A         |
| Order number          | A531231                           |
| EAN                   | 8595155002709                     |
| Barva                 | green-yellow                      |
| Package (small) [pcs] | 20 ks v krabici / 20 pcs in a box |

**Technical data**
**Electrical parameters**

|  |      |
|--|------|
| Nominal current [A] CE                     | -    |
| Nominal current [A] Ex                     | -    |
| Shor-time current[A]                       | 480  |
| Nominal insulation voltage [V] CE          | -    |
| Nominal insulation voltage [V] Ex          | -    |
| Nominal working voltage Ue [V]             | -    |
| Nominal impulse withstand voltage Uimp [V] | 4000 |

**Conductor connection**

|   |           |
|---|-----------|
| Nominal cross section input / output [mm <sup>2</sup> ] | 1 / 1     |
| Range of conductors, input / output [mm <sup>2</sup> ]  | 0,5 ÷ 6   |
| Conductor cross section solid [mm <sup>2</sup> ]        | 0,5 ÷ 6,0 |
| Conductor cross section flexible [mm <sup>2</sup> ]     | 0,5 ÷ 4,0 |
| 2 conductors cross section solid [mm <sup>2</sup> ]     | -         |
| 2 conductors cross section flexible [mm <sup>2</sup> ]  | -         |
| 3 conductors cross section solid [mm <sup>2</sup> ]     | -         |
| 3 conductors cross section flexible [mm <sup>2</sup> ]  | -         |
| Stripping length input / output [mm]                    | 10        |
| Number of clamping units                                | 2         |
| Number of poles / number of floors [pcs]                | 1 / 1     |

**Mechanical parameters**

|             |                            |
|-------------|----------------------------|
| Torque [Nm] | 0,5                        |
| Tool        | Screwdriver/ PH0 / 0,5 x 3 |
| Mounting    | TH 35                      |

**Operating parameters**

|                            |            |
|----------------------------|------------|
| Pollution degree           | 2          |
| IP                         | -          |
| Operating temperature [°C] | -40 ÷ +105 |
| The need for an end plate  | no         |

**Approvals**

|      |                   |
|------|-------------------|
| Norm | CE: IEC 60947-7-2 |
|------|-------------------|

ATEX approvals


-

**Dimensions and weight**

|                  |      |
|------------------|------|
| Height [mm]      | 7,4  |
| Length [mm]      | 39,4 |
| Weight / NET [g] | 48,0 |
| Weight / NET [g] | 25   |

## Other information

---



### **ELEKTRO, výrobní družstvo v Bečově nad Teplou**

Tovární 128, 364 64 Bečově nad Teplou

IČ: 000 28 886

DIČ: CZ 000 28 886

25.06.2024

